

TECHNICAL DATA

All the facts at a glance



TYPE

IP Camera OC 1280P | Article-Nr.: 5929

TECHNICAL DETAILS

- Integrated LAN/WiFi unit and 868MHz radio transmitter/receiver
- Compatible with Olympia 6xxx/9xxx alarm systems
- Plug & Play installation in P2P process
- 67° camera detection angle, pivotable: 330° horizontal / 80° vertical
- Audio und video intercom function via smartphone
- Push messaging on app
- 11 IR LEDs for night vision up to 10 metres
- MicroSD card slot
- H.264 compression, 1,280 x 720 pixel resolution
- Ethernet 10/100Mbps RJ-45 / WiFi 802.11 b/g, WEP&WPA encryption
- Power supply via external power adapter
- Permitted ambient conditions: 0 °C to +55 °C at 20 % to 85 % humidity
- Transmission frequency: 868.5 MHz (radio), 2.4 GHz (WiFi)
- Transmission power (max.): 1 mW (radio), 63 mW (WiFi)
- Power supply input: 100 - 240 V, 50/60 Hz, 0.5 A / output: 5 V, 2,000 mA / 5 W
- Lens / sensor: 1/4" CMOS sensor (colour)
- Resolution: 1,280 x 720 pixels
- Image compression: H.264
- Light sensitivity: 0.5 Lux
- Image frequency rate: 30 fps max.
- Night vision: 8 IR LEDs, range up to 15 m
- Pivot range / angle of vision: 330° horizontal, 90° vertical / 60°
- Motion detection: yes
- Microphone / loudspeaker: yes/yes
- Interfaces: microSD, I/O
- LAN: 10 base-T Ethernet / 100 base-TX Fast Ethernet
- WiFi: 802.11 b, 802.11 g, 802.11 n
- Encryption: WEP, WPA and WPA2

DIMENSIONS

Diameter 65 mm x Length 175 mm

WEIGHT

350 Gramm

FASTENING

Wall mounting required.

