TECHNICAL DATA
All the facts at a glance

TYPE
IP Camera OC 1280P | Article-Nr.: 5929

TECHNICAL DETAILS
• Integrated LAN/WiFi unit and 868MHz radio transmitter/receiver
• Compatible with Olympia 6xxx/9xxx alarm systems
• Plug & Play installation in P2P process
• 67° camera detection angle, pivotable: 330° horizontal / 80° vertical
• Audio und video intercom function via smartphone
• Push messaging on app
• 11 IR LEDs for night vision up to 10 metres
• MicroSD card slot
• H.264 compression, 1,280 x 720 pixel resolution
• Ethernet 10/100Mbps RJ-45 / WiFi 802.11 b/g, WEP&WPA encryption
• Power supply via external power adapter
• Permitted ambient conditions: 0 °C to +55 °C at 20 % to 85 % humidity
• Transmission frequency: 868.5 MHz (radio), 2.4 GHz (WiFi)
• Transmission power (max.): 1 mW (radio), 63 mW (WiFi)
• Power supply input: 100 - 240 V, 50/60 Hz, 0.5 A / output: 5 V, 2,000 mA / 5 W
• Lens / sensor: 1/4" CMOS sensor (colour)
• Resolution: 1,280 x 720 pixels
• Image compression: H.264
• Light sensitivity: 0.5 Lux
• Image frequency rate: 30 fps max.
• Night vision: 8 IR LEDs, range up to 15 m
• Pivot range / angle of vision: 330° horizontal, 90° vertical / 60°
• Motion detection: yes
• Microphone / loudspeaker: yes/yes
• Interfaces: microSD, I/O
• LAN: 10 base-T Ethernet / 100 base-TX Fast Ethernet
• WiFi: 802.11 b, 802.11 g, 802.11 n
• Encryption: WEP, WPA and WPA2

DIMENSIONS
Diameter 65 mm x Length 175 mm

WEIGHT
350 Gramm

FASTENING
Wall mounting required.

Olympia Business Systems Vertriebs GmbH, Zum Kraftwerk 1, D-45527 Hattingen
www.olympia-vertrieb.de